

Flanged-head wood screw

Technical configuration sheet | 29.09.2026

Material: Stainless steel A2

Diameter (mm)	Length l (mm)	Thread b (mm)	Head dk (mm)	Head height k (mm)	Drive
6	30	20	15	3.8	TX25
6	35	24	15	3.8	TX25
6	40	24	15	3.8	TX25
6	45	30	15	3.8	TX25
6	50	30	15	3.8	TX25
6	55	36	15	3.8	TX25
6	60	36	15	3.8	TX25
6	65	42	15	3.8	TX25
6	70	48	15	3.8	TX25
6	80	54	15	3.8	TX25
6	90	70	15	3.8	TX25
6	100	70	15	3.8	TX25
6	110	70	15	3.8	TX25
6	120	70	15	3.8	TX25
6	130	70	15	3.8	TX25
8	30	Fully threaded	20	4.6	TX40
8	35	Fully threaded	20	4.6	TX40
8	40	Fully threaded	20	4.6	TX40
8	45	Fully threaded	20	4.6	TX40
8	50	Fully threaded	20	4.6	TX40
8	55	Fully threaded	20	4.6	TX40
8	60	50	20	4.6	TX40
8	65	50	20	4.6	TX40
8	70	50	20	4.6	TX40
8	80	72	20	4.6	TX40

Diameter (mm)	Length l (mm)	Thread b (mm)	Head dk (mm)	Head height k (mm)	Drive
8	90	80	20	4.6	TX40
8	100	80	20	4.6	TX40
8	110	80	20	4.6	TX40
8	120	80	20	4.6	TX40
8	130	80	20	4.6	TX40

RFQ / Project enquiry

Specify the component, dimensions, quantity, roof covering and module details. Supply configuration and compatibility are confirmed for the individual project.

This sheet does not replace installation instructions or structural design checks.