


DIN 982

High nylon-insert lock nut

A nylon insert retained in the upper collar provides prevailing torque during assembly. Coarse- and fine-pitch designs are listed in the table: always specify diameter × pitch.

Reference sizes are listed in the table. Other diameters, pitches, materials and finishes are available on request, subject to an agreed supply specification.



d: nominal thread · P: pitch · s: width across flats · m: body height · h: overall height · dc: flange diameter. Only columns included in the table apply.

Identification drawing, not a manufacturing drawing.

Dimensional range

Dimensions in millimetres.

M	Pitch P	s	h	m
5	0.8	8	6.3	3.5
6	1	10	8	4.5
8	1.25	13	9.5	6.5
8	1	13	9.5	6.5
10	1.5	17	11.5	8
10	1.25	17	11.5	8
10	1	17	11.5	8
12	1.75	19	14	10
12	1.5	19	14	10
12	1.25	19	14	10
14	2	22	16	11
14	1.5	22	16	11
16	2	24	18	12.8
16	1.5	24	18	12.8
18	1.5	27	20	14.4
20	1.5	30	22	16
22	1.5	32	25	17.6
24	2	36	28	19
27	2	41	31	21.6
30	2	46	33	24
33	2	50	35	24
36	3	55	39	28
39	3	60	42	31
42	3	65	45	33
45	3	70	47	36
48	3	75	50	38

Materials and classes

Material	Class / hardness	M	Supply
Steel to mechanical specification	8	M5–M48	On request

Finishes and treatments

Finish	Material	Class	M
Electroplated zinc	Steel to mechanical specification	8	M5–M48

Select the finish for the material/property-class combination. Hydrogen relief and lubrication are separate process requirements, not certificates and not implied by the coating name.



Standards, documents and enquiry

Non-metallic insert: check temperature, chemicals and coating compatibility. Prevailing torque is not preload. Reuse and acceptance criteria must follow the manufacturer specification; no universal reuse count is assigned.

Non-metallic insert: check temperature, chemicals and coating compatibility. Prevailing torque is not preload. Reuse and acceptance criteria must follow the manufacturer specification; no universal reuse count is assigned.

UNI 7473

Related reference; compare dimensions, design and mechanical specification before substitution. Exact equivalence is not claimed.

ISO 7040

Related coarse-pitch reference; not assigned to the fine-pitch rows of this sheet.

Supply documentation

Declaration of conformity; Material certificate; EN 10204 2.2 test report; EN 10204 3.1 inspection certificate; Dimensional inspection report; Coating report; Other documentation

Documents are subject to order agreement; no batch certificate is automatically included.

Related components

ISO 4032, ISO 4014. Match bolt and nut diameter and pitch. Links to other families do not declare compatibility of every thread.

Request a quote

Specify standard, diameter, pitch and length where applicable, material, property class or hardness, finish, quantity and documents. Other sizes and dedicated production can be assessed on request, with agreed minimum quantities.

Reference technical configurations: these do not represent stock quantities.

Other materials and specifications

For requirements beyond the tabulated combinations, enquire about aluminium, brass, nylon, duplex, superduplex or an ASTM specification. Alloy or grade, dimensions, mechanical requirements and finish are defined for the enquiry; the geometric reference does not automatically imply conformity with the product standard.