Hexalobular socket tapping screw with integral washer head

ST tapping thread for pre-drilled sheet metal. Geometry, executions and materials are shown separately; enter the required length freely in the quotation request.


Integral washer head TX

Dimensional reference: Integral washer head TX · Thread: ST · Drive: TX · Units: mm



Representative geometry photograph. Material and finish are specified separately.

Technical drawing



A	Head diameter
H	Head height
D	External thread diameter
P	Indicative pitch
U	Integral washer thickness
TX	Hexalobular recess number
d	Thread root diameter.
G	End portion identified in the drawing.
R	Fillet radius.
Q	Recess depth.
M	Recess width.
L / l	Length to specify in the enquiry; not listed in the table.

https://www.dueemmesidol.it/en/products/standard-fasteners/tapping-screws/rondella-incorporata-tx/

Reference geometry

Dimensions in mm. Supply lengths are not listed: specify the required length in your enquiry.

Dimensions of the Kilton execution identified in the sources. The ~ symbol denotes an approximate value. The table identifies geometry, not availability. For ISO executions, other point forms or a PZ recess, check differences on the variant drawing.

Thread	Limit	A	H	D	P	U	TX
ST 2,9	Min.	6,92	2,10	2,76	1,10	0,70	T10
ST 2,9	Max	7,50	2,35	2,90	1,10	0,70	T10
ST 3,5	Min.	8,42	2,35	3,35	1,30	0,80	T15
ST 3,5	Max	9,00	2,60	3,53	1,30	0,80	T15
ST 3,9	Min.	9,42	2,55	3,73	1,40	1,00	T15
ST 3,9	Max	10,00	2,80	3,91	1,40	1,00	T15
ST 4,2	Min.	9,42	2,75	4,04	1,40	1,00	T20
ST 4,2	Max	10,00	3,05	4,22	1,40	1,00	T20
ST 4,8	Min.	10,80	3,25	4,62	1,60	1,20	T25
ST 4,8	Max	11,50	3,55	4,80	1,60	1,20	T25
ST 5,5	Min.	12,30	3,50	5,28	1,80	1,40	T25
ST 5,5	Max	13,00	3,80	5,46	1,80	1,40	T25
ST 6,3	Min.	13,80	4,25	6,02	1,80	1,60	T30
ST 6,3	Max	14,50	4,55	6,25	1,80	1,60	T30

Materials, grades, finishes and treatments

Material	Requirements	Finish
Case-hardened / hardened steel	Tapping screw requirements; specify execution	Cr(III) zinc plated

Material, coating, hardness and execution are confirmed in the quotation. Not all combinations are implied. Metric screw property classes such as 8.8 must not be automatically transferred to tapping screws.

Documentation

Document	Status
Declaration of conformity	Subject to order agreement
Material certificate	Subject to order agreement
EN 10204 2.2 test report	Subject to order agreement
EN 10204 3.1 inspection certificate	Subject to order agreement
Dimensional inspection report	Subject to order agreement
Coating report	Subject to order agreement
Other documentation	Subject to order agreement

Batch documents are not automatically included: specify your requirements in the RFQ.

Standards, executions and application

The screw forms its thread in a prepared hole: it is not self-drilling. Pilot-hole diameter, sheet thickness and material must be checked by assembly trials; no universal pilot-hole size is specified. ST thread is distinct from metric M thread. Related DIN, UNI and ISO references do not declare dimensional identity.

Cone point; other executions require drawing verification.