
Conical seat, concave type D


Conical seat, concave type D for assemblies and replacement parts. Compare the required geometry and specify material, finish and supply requirements in your enquiry.

DIN 6319 D

Type: Conical seat, concave type D · Reference: DIN 6319 D · Dimensions: Dimensions in millimetres · Configuration: Material and finish to specification



Technical drawing



d1: bore diameter · d2: outside diameter · d3: dimension d3 · h: height

Identification drawing, not a manufacturing drawing. Refer to the agreed drawing for construction details, tolerances and free heights.

Variants and dimensions

Dimensions in mm. M identifies the screw nominal size.

Different geometries may exist for the same nominal size: specify the required dimensions. Tolerances and omitted details must be defined in the specification.

For screw	d1	d2	d3	h
M6	7.1	12	11	2.8
M8	9.6	17	14.5	3.5
M10	12	21	18.5	4.2
M12	14.2	24	20	5
M14	16.5	28	24.8	5.6
M16	19	30	26	6.2
M18	21	35	-	7
M20	23.2	36	31	7.5
M22	26	42	-	9.5
M24	28	44	37	9.5
M27	32	50	-	12
M30	35	56	49	12
M33	38	62	-	15
M36	42	68	60	15

Materials, classes, finishes and treatments

Material	Class / hardness	Finishes / treatments
Case-hardened steel	To specify	Plain; Zinc plated
Stainless steel A2	To specify	To specify
Stainless steel A4	To specify	To specify

Material, hardness and treatment must be specified for the requested execution. A2 and A4 identify the stainless steel group and do not automatically imply 70/80 strength classes, hardness or passivation.

Dueemme confirms size, material and finish combinations and availability in its quotation.

Documentation

Document	Status
Declaration of conformity	Subject to order agreement
Material certificate	Subject to order agreement
EN 10204 2.2 test report	Subject to order agreement
EN 10204 3.1 inspection certificate	Subject to order agreement
Dimensional inspection report	Subject to order agreement
Coating report	Subject to order agreement
Other documentation	Subject to order agreement

Batch documents are not automatically included: specify your requirements in the RFQ.

Standards, types and application

DIN 6319 D

Suitability depends on bearing surfaces, preload and service conditions; washer geometry alone does not guarantee preload retention.

State the standard and edition or attach a drawing. Related DIN, ISO, UNI and NF references do not constitute a universal equivalence declaration for every execution.