
Round head TX chipboard screw with collar

Geometry, drive and characteristics of documented executions. Materials and finishes are shown separately; enter the required length freely in your quotation request.

Wood screws


Dimensional reference: Wood screws · Thread: Wood thread · Drive: TX · Units: mm



Representative geometry photograph. Material and finish are specified separately.

Technical drawing and legend

Ambrovit reference execution 08062



A	Head diameter
H	Head height
d1	Underhead collar diameter
P	Thread pitch
TX	Hexalobular recess number

Dimensions

Ambrovit reference execution 08062

Dimensions in mm, except drive size. Min./Max. and approximate values follow the source. Tables apply to the indicated executions and must not be extended automatically to other products. Availability is confirmed in the quotation.

Nominal diameter	Limit	A	H	d1	P	TX
5,5	Min.	11,50	2,85	5,70	~2,20	T30
5,5	Max	12,20	3,20	5,90	~2,20	T30
6,0	Min.	14,50	3,00	5,80	~2,70	T30
6,0	Max	15,00	3,40	6,00	~2,70	T30
7,0	Min.	16,50	3,40	6,80	~3,30	T30
7,0	Max	17,00	3,80	7,00	~3,30	T30

Materials and finishes

Executions documented by the named suppliers. Material and coating are confirmed in the quotation; a finish does not imply every diameter and geometry combination.

Material	Finish	Reference
C1022 steel	Zinc plated Cr3; Yellow zinc plated Cr3; Black zinc plated Cr3	Ambrovit 08062

Documentation

Document	Status
Declaration of conformity	Subject to order agreement
Material certificate	Subject to order agreement
EN 10204 2.2 test report	Subject to order agreement
EN 10204 3.1 inspection certificate	Subject to order agreement
Dimensional inspection report	Subject to order agreement
Coating report	Subject to order agreement
Other documentation	Subject to order agreement

Batch documents are not automatically included: specify your requirements in the RFQ.

Executions and application

Specify the timber type and density, the panel or component to be fixed, the manufacturer-required pilot hole and edge/end distances. No universal pilot-hole diameter is assigned. Wood drill-point versions do not imply steel drilling capability.

Technical references

Ambrovit 08062